

# LP 502030 Lithium Polymer Battery

## Brief Datasheet

### 1 BASIC SPECIFICATION

1	Battery Type	LP 502030	
2	Nominal Capacity	Typical	250mAh (0.2C discharge)
		Minimum	230mAh (0.2C discharge)
3	Nominal Voltage	3.7V(0.2C discharge)	
4	Charging Voltage	4.2V±0.05V	
5	Standard Charge	Method: CC/CV (constant current/constant voltage) Current:115mA (0.5C) Voltage:4.2V EndCurrent:4.6mA (0.02C)	
6	Maximum Charge Current	230mA (1C)	
7	Standard Discharge	Method: CC (constant current) Current:46mA (0.2C) End Voltage:2.75V	
8	Maximum Discharge Current	460mA (2C)	
9	Weight	Approx.5.5± 1.0g	
10	Operating temperature	Charge: 0°C to 45°C Discharge: -20°C to 60°C	
11	Storage Temperature	-20°C to 45°C	
12	Cycle life	500cycles (at 0.5C charge and discharge, 23°C)	


Note: 1C = 1 Capacity

### 2 MAIN FEATURES

- Thin format, light weight, large area, and flexibility in design.
- Easily customized, Energy density, High capacity.

### 3 WARNING

- Do not overcharge, force charge, short circuit, disassemble, deform, heat or place the battery near a direct flame. Any of the above actions could cause it to ignite, explode or become damaged.
- Keep this battery out of the reach of children.
- When storing the battery or throwing it away, be sure to cover with tape.



# Li-Polymer