

A

B

C

D

E

NOTES:

1. MATERIAL

- 1.1 Insulator: PBT +30% Glass Fiber, UL94V-0
- 1.2 Color: Black
- 1.3 Contact: Brass
- 1.4 Contact Plated: Gold-flash over nickel plated
- 1.5 Dip area plated: Tin plated or Gold-flash
- 1.6 Shell: SPCC plate with nickel plated
- 1.7 Screw: Copper Alloy with nickel plated

2. SPECIFICATION

- 2.1 Dielectric Strength: 500V for one minute
- 2.2 Insulator Resistance: 1000MΩ Min. at 500V DC
- 2.3 Contact Resistance: 20mΩ max.
- 2.4 Temperature: -55℃ ~ +105℃
- 2.5 Rated Current: 5Amp

PART NO.

CDBR

XX

M

XX

-

Contact:

Type:

T : Jack Screw Insert

UN : Rivet

U : Rivet & Jack Screw Attached




UT : Rear & Jack Screw Insert

*: Gold Flash / Tin plated
2: Gold Flash

Male

Pin Size

Series No. D-SUB 90°

T Type	UN & U Type	UT Type
叉鎖	鉚合不附螺絲 鉚合附螺絲	鉚合鎖螺絲
		

Poles	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25
09	30.80	25.00	16.92	8.30	12.60
15	39.20	33.32	25.25	8.30	12.60
25	53.05	47.04	38.96	8.30	12.60
37	69.40	63.50	55.42	8.30	12.60

DESCRIPTION(內容):

D-SUB 90° (Male) 雙排
半金. 全金 (黑)PART NO:
(料 號)

CDBRXXMXX-

DWG NO(圖號):

DRAWN(製圖):

GONG

CHECKED(確認):

TERESA

APPROVAL(核准):

JOHNNY

GENERAL TOLERANCE:

(公差)

.0 ±0.1
.00 ±0.02
.000 ±0.03

SCALE(比例):

FREE

REV:

R0

UNIT:

mm

SIZE:

A4

SHEET:

1/1

REV

R0

R1

R2

R3

DESCRIPTION

RELEASE

DATE

2014.12.16

A

B

C

D

E