



**Specifications**

Current Rating	:3 Amps
Insulator Resistance	:5000 Megohms min.
Dielectric Withstanding	:AC 1000 V
Operating Temperature	:-40°C ~ +105°C
Max Processing Temp	:260°C for 3~5 sec Max.
Contact Material	:Copper Alloy
Insulator Material	:Polyester, UL 94V-0
Standard	:Nylon-6T
Finish	:Tin, Gold Plated
Standard	:Gold Flash all over

**How to order**

Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts
<u>P101</u>	- <u>X</u>	<u>X</u>	<u>X</u>	- <u>A / B</u>	- <u>XX</u>
(Pin Header Single Row) P101 (H:2.54)	K: "K" Type	G: Gold Flash T: Tin Plated A: 10U"Gold B: 15U"Gold C: 20U"Gold I: 30U"Gold (Standard: G)	N: Nylon-6T (Standard: N)	A (060) B (047) (If you desire on other length, by marking put desired in the A/B)	(02 TO 40 Contacts)

Dim(6.0/4.7) :

A: \_\_\_\_\_ B: 4.7

△ 此符號表示重點管控尺寸

	DESCRIPTION(內容): <b>2.54mm Pin Header H:2.54 臥貼式</b> □ = 0.64 Nylon-6T	DRAWN(製圖):	GENERAL TOLERANCE:(公差)	REV: <b>A1</b>	REV	DESCRIPTION	DATE
	PART NO: (料號)	CHECKED(確認):	X. ±0.30 X.° ±5.0° .X ±0.20 .X° ±3.0° .XX ±0.15 .XX° ±1.0°	UNIT: <b>mm</b>	<b>1</b>		
	DWG NO(圖號):	APPROVAL(核准):	SCALE(比例): 1:XX	SIZE: <b>A4</b>	<b>2</b>		
				SHEET: <b>1/1</b>	<b>3</b>		
					<b>4</b>		