



Specifications

Current Rating	:3 Amps
Insulator Resistance	:5000 Megohms Min.
Dielectric Withstanding	:AC 1000 V
Operating Temperature	:-40°C ~ +105°C
Contact Material	:Copper Alloy
Insulator Material	:Polyester, UL 94V-0

Finish: Tin, Gold Plated
 Standard: Gold Flash all over

How to order

Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts
<u>P22X</u>	- <u>X</u>	<u>X</u>	<u>X</u> -	<u>A / C / B</u>	- <u>XX</u>
(Pin Header Dual Row)	R:Right Angle Type (Down Angle Type) R1:1.5mm	G:Gold Flash T:Tin Plated A:10U°Gold B:15U°Gold C:20U°Gold (Standard:G)	P:PBT N:Nylon-6T	A C B (060) (030) (030) (If you desire on other length, by marking put desired in the A/C/B) (Standard:060/000/030)	(04 TO 80 Contacts)

Selectivity:

- P221 (H:2.54 W:5.08) (Material (Standard): PBT)
- P222 (H:1.7 W:5.08) (Material: Nylon-6T)
- P223 (H:1.5 W:5.08) (Material: Nylon-6T)

Dim(6.0/3.0/3.0):

A: _____ C: _____ B: _____.

△ 此符號表示重點管控尺寸

DESCRIPTION(內容): 2.54mm Pin Header 90° □=0.64 雙塑雙排 PART NO: (料號) DWG NO(圖號):	DRAWN(製圖):	GENERAL TOLERANCE: (公差)	REV: A1	REV	DESCRIPTION	DATE
	CHECKED(確認):	X. ±0.30 X.° ±5.0° .X ±0.20 .X° ±3.0° .XX ±0.15 .XX° ±1.0°	UNIT: mm	1		
	APPROVAL(核准):	SCALE(比例): 1:XX	SIZE: A4	2		
			SHEET: 1/1	3		
				4		