



SPECIFICATION:

PITCH BETWEEN POLES : 2.5mm

CURRENT RATING : 3A

VOLTAGE RATING : 250V

CONTACT RESISTANCE : INITIAL VALUE/10mΩ max.

AFTER ENVIRONMENTAL TESTING/20mΩ max.

INSULATION RESISTANCE :1000 MΩ (min.)

WITHSTAND VOLTAGE : 800V AC/MINUTE

TEMPERATURE RANGE : -25°C TO +85°C

APPLICABLE WIRE: AWG #22 TO #30

FEATURES:

AVAILABLE NUMBER OF CIRCUITS 2 TO 15

MATERIAL : NYLON 66 UL94V-0

Poles	PART NO.	DIM:(mm)	
		A	B
02	CE-H250-02	2.50	7.00
03	CE-H250-03	5.00	9.50
04	CE-H250-04	7.50	12.00
05	CE-H250-05	10.00	14.50
06	CE-H250-06	12.50	17.00
07	CE-H250-07	15.00	19.50
08	CE-H250-08	17.50	22.00
09	CE-H250-09	20.00	24.50
10	CE-H250-10	22.50	27.00
11	CE-H250-11	25.00	29.50
12	CE-H250-12	27.50	32.00
13	CE-H250-13	30.00	34.50
14	CE-H250-14	32.50	37.00
15	CE-H250-15	35.00	39.50

所有材料為  
"環保材料"

2006.7.10

RoHS

DESCRIPTION(內容):	DRAWN(製圖):	GENERAL TOLERANCE:	REV:	REV	DESCRIPTION	DATE
EH2.5mm HOUSING	GONG	.000 ±0.08 .00 ±0.13 .0 ±0.25	R3	R0	變更環保章字樣	2006.08.17
	CHECKED(確認):		UNIT:	R1	修改接觸阻抗單位	2006.11.18
PART NO: (料號) CE-H250-XX	Mandy	SCALE(比例):	mm	R2	修改圖框	2007.05.21
DWG NO(圖號): 2505-H	APPROVAL(核准):	FREE	A4	R3	2014年料號P數編碼統一兩碼	2014.12.19
	Johnny		SHEET:			
			1/1			