



### Specificatis

Current Rating	: 2A AC, DC
Voltage rating	: 100V AC, DC
Temperature range	: -25°C ~ +85°C
Contact resistance	: 10mΩ Max
Insulation resistance	: 1000MΩ Min
Withstanding voltage	: 800 V AC/minute
Pin Material	: Brass
Finished	: Tin-plated
Housing Mateial	: Nylon-66, UL94 V-0
Color	: Ivory-white



Circuits	Patr NO	Dimension mm		
		A	B	C
2	CP-W20-02	2.00	6.00	4.84
3	CP-W20-03	4.00	8.00	6.84
4	CP-W20-04	6.00	10.00	8.84
5	CP-W20-05	8.00	12.00	10.84
6	CP-W20-06	10.00	14.00	12.84
7	CP-W20-07	12.00	16.00	14.84
8	CP-W20-08	14.00	18.00	16.84
9	CP-W20-09	16.00	20.00	18.84
10	CP-W20-10	18.00	22.00	20.84
11	CP-W20-11	20.00	24.00	22.84
12	CP-W20-12	22.00	26.00	24.84
13	CP-W20-13	24.00	28.00	26.84
14	CP-W20-14	26.00	30.00	28.84
15	CP-W20-15	28.00	32.00	30.84
16	CP-W20-16	30.00	34.00	32.84
17	CP-W20-17	32.00	36.00	34.84
18	CP-W20-18	34.00	38.00	36.84

注: 10PIN(含10PIN)以下需打牙

DESCRIPTION(內容): <b>2.0mm Wafer 180° □=0.50 打K</b> (環保材料)	DRAWN(製圖): 王建平	GENERAL TOLERANCE: (公差)	REV: A/9	REV	DESCRIPTION	DATE	
	CHECKED(確認):	.0 ±0.20 .00 ±0.15 .000 ±0.10	UNIT: mm	1	△此符號表示重點管控尺寸	2005.08.13	
	PART NO: (料號) CP-W20-XX	APPROVAL(核准):	SCALE(比例): 1:XX	SIZE: A4	2	(1D)增加產品顏色標注	2007.06.26
	DWG NO(圖號):			SHEET: 1/1	3	增加Layout尺寸上的公差	2009.09.04
				4	增加塑膠內徑尺寸	2012.10.18	