



## SPECIFICATIONS

### Electrical

Current Rating: 5A AC, DC  
 Voltage Rating: 250V AC, DC  
 Operating Temp.: -25°C ~ +85°C  
 Insulation Resistance: 1000mΩ / min.  
 Dielectric Withstanding Voltage: 1500V AC / min.  
 Contact Resistance: 10mΩ / max.

### Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
02	3.96	8.45	CW-H396-02	
03	7.92	12.39	CW-H396-03	
04	11.88	16.35	CW-H396-04	
05	15.84	20.31	CW-H396-05	
06	19.80	24.27	CW-H396-06	
07	23.76	28.23	CW-H396-07	
08	27.72	32.19	CW-H396-08	
09	31.68	36.15	CW-H396-09	
10	35.64	40.11	CW-H396-10	
11	39.60	44.07	CW-H396-11	
12	43.56	48.03	CW-H396-12	
13	47.52	51.99	CW-H396-13	
14	51.48	55.95	CW-H396-14	
15	55.44	59.91	CW-H396-15	
16	59.40	63.87	CW-H396-16	
17	63.36	67.83	CW-H396-17	
18	67.32	71.79	CW-H396-18	
20	75.24	79.71	CW-H396-20	

所有材料為  
"環保材料"  
2006. 6. 29  
RoHS

DESCRIPTION(內容):	DRAWN(製圖):	GENERAL TOLERANCE:	REV:	REV	DESCRIPTION	DATE
3.96mm Wire-to-Board Housing	GONG	X.XX ± 0.35 X.X ± 0.5	R3	R0		2006.03.20
	CHECKED(確認):		UNIT:	R1	環保料	2006.06.29
PART NO:	APPROVAL(核准):	SCALE(比例):	mm	R2	變更環保章字樣	2007.06.07
(料號) CW-H396-XX			JOHNNY	FREE	R3	2014年料號P數編碼統一兩碼
DWG NO(圖號): 3960-XX			SIZE: A4			
			SHEET: 1/1			