


所有材料為
"環保材料"
2013.1.24
RoHS

SPECIFICATIONS

Current rating: 1A AC, DC.
Voltage rating: 100V AC, DC.
Temperature range: -25°C to +85°C
Contact resistance: 20mΩ Max.
Insulation resistance: 500MΩ Min.
Withstanding voltage: 500V AC/minute.
Material: Nylon 66, UL94V-0.

Part NO.	Circuit No.	Dimensions	
		A	B
CZ-H15-02A	02P	1.50	4.50
CZ-H15-03A	03P	3.00	6.00
CZ-H15-04A	04P	4.50	7.50
CZ-H15-05A	05P	6.00	9.00
CZ-H15-06A	06P	7.50	10.50
CZ-H15-07A	07P	9.00	12.00
CZ-H15-08A	08P	10.50	13.50
CZ-H15-09A	09P	12.00	15.00
CZ-H15-10A	10P	13.50	16.50
CZ-H15-11A	11P	15.00	18.00
CZ-H15-12A	12P	16.50	19.50
CZ-H15-13A	13P	18.00	21.00
CZ-H15-15A	15P	21.00	24.00

DESCRIPTION(內容): 1.50mm Wire-to-Board Housing (方孔型) PART NO: (料號) CZ-H15- <u>XXA</u> DWG NO(圖號): A1500H-XP	DRAWN(製圖): GONG	GENERAL TOLERANCE: (公差) .X ±0.25 .XX ±0.15 .XXX ±0.05	REV: R1	REV	DESCRIPTION	DATE	
	CHECKED(確認): MANDY		UNIT: mm	R0		RELEASE	2013.01.24
	APPROVAL(核准): JOHNNY	SCALE(比例): FREE		SIZE: A4	R1	2014料號P數編碼統一兩碼	2014.12.19
				SHEET: 1/1	R2 R3		